



New – the lightest and fastest tool for staples type 180 in the market!



BeA Stapler 180/65-835C

- At only 2,7 kg the lightest tool in the market for staples type 180
- Fast shot sequence
- Extremely powerful
- New ergonomic handgrip, operator friendly
- Adjustable exhaust
- Depth control adjustment
- New magazine design for faster loading
- Quick release front nose
- Slim nose design for a high degree of access and accuracy
- Available with contact actuation or with single shot actuation
- Accepts all staples type 180 from 40 - 65 mm (15 gauge, 1⁵/₈ to 2⁵/₈) (VZ HZ, NR HZ, NK HZ) and Q 180



Applications

Prefabricated house industry, framing, roofing, flooring, truss building etc.

BeA 180/65-835C

Technical Data




Type description	180/65-835C Standard
Item code	12000500
Magazine type	Top loader
Safety system	Contact actuation*
Fastener type	Type 180 (15 gauge)
Magazine capacity	Max. 157 staples
Fasteners per strip	2 x 60 (VZ HZ = 3 x 40)
Operating pressure	6 - 8 bar (90 - 120 psi)
Max operating pressure	8 bar (120 psi)
Air consumption /operation	2,9 litre / 6 bar
Inner hose diameter	Ø 9 - 10 mm recommended
Emmission sound pressure level at the workstation	L pA, 1s, d = 82 dB
Single-shot emmission sound pressure level	L pA, 1s, d = 89 dB
Weight	2.70 kg (5 lbs 15 oz)
Vibration level as per ISO 8662-1 1 is 3,2 m/s ² .	
Accessories supplied with the tool	Operating instructions, spare parts list, service instructions, allen wrenches; air connector

Subject to technical modifications

*Also available with single shot actuation set: item no. 14408803

Staples Type 180



Description	L = Length (mm)
180/40 NK HZ	40 (1 5/8)
180/45 NK HZ	45 (1 3/4)
180/50 NK HZ	50 (2')
180/55 NK HZ	55 (2 1/8)
180/60 NK HZ	60 (2 3/8)
180/63 NK HZ	63 (2 7/16)
180/65 NK HZ	65 (2 5/8)

Joh. Friedrich Behrens AG
Industrial Fastening Systems
Bogenstraße 43 - 45
22926 Ahrensburg
Germany

Further information:
Phone: +49 (0) 41 02 78 - 444
Fax +49 (0) 41 02 78 - 270
eMail: info@bea-group.com
www.Bea-Group.com

Staples type 180 are available in VZ HZ + NR HZ and are certified to DIN 1052.

BeA is a member of following associations:

