

Pneumatic Nailer Type WM 12-156

The compact and well balanced nailer drives corrugated fasteners type WM in lengths from 6 to 12 mm. It satisfies a multitude of fastening requirements and is the perfect solution when fastening butt and corner joints. Used in conjunction with an attachment this tool can perform invisible fastening of inner-corner joints.



Popular applications:

Butt and corner jointing in furniture, windows and doors.

Length: 258 mm

Width: 70 mm

Height: 261 mm

Technical data

Type description:	WM 12 -156
Article code:	12000126
Magazine type :	Top loader
Safety:	Contact actuation
Fastener type:	Corrugated Fasteners Type WM
Magazine capacity:	75
Fasteners per strip:	3 x 24
Operating pressure:	6 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	1.5 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d = 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d = 87 dB
Weight:	2.8 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 4 m/s².

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, silencer

Subject to technical modifications.

Accessories:

Article code	Description
14403409	Remote valve with safety yoke
14403402	Remote valve
14403442	Mounting flange
14406090	Attachment for corner joints
14401767	Piston complete
14406201	Single actuation set
14406959	Grip elongation

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Nailer Type WM 12-156

Corrugated fasteners Type WM



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: +49 (0) 4102 78-0
Fax: +49 (0)4102 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



Description	L = Length mm
WM 06 BK A	6
WM 09 BK A	9
WM 12 BK A	12

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut