

Pneumatic Pinner Type S 125-569

The compact lightweight BeA pneumatic pinner drives headless pins Ø 1.1 mm in the lengths of 14 – 25 mm. A tool for multitude of uses in the woodworking industry and other applications where headless pins are required. The tool is precision made with a long service life.



Popular applications:

Interior moulding, panels, furniture industry, picture frames, caravan assembling and associated trades.

Length: 207 mm
Width: 47 mm
Height: 180 mm

Technical data

Type description:	S 125-569 Standard
Article code:	12000439
Magazine type :	Side loader
Safety:	-
Fastener type:	Pins Type S 100
Magazine capacity:	126
Fasteners per strip:	2 x 50
Operating pressure:	5 – 6 bar
Max. operating pressure:	6 bar
Air consumption/operation:	0.45 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 80 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 88 dB
Weight:	1.06 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

Accessories:

Articel code	Description
14405569	Remote valve
14405571	Mounting flange

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Pinner Type S 125-569

Pins type S 100



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



Description	L = Length mm
S 114 NK	14
S 116 NK	16
S 119 NK	19
S 122 NK	22
S 125 NK	25

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut