



Extremely powerful -
perfect for pallet
production



For wire collated BDC nails

BeA pneumatic nailer DC/90-902C

For nails:

BDC Ø 2,5 - 3,4 mm in the lengths of 50 - 90 mm

- Extremely powerful and sturdy tool
- Magnesium housing
- 360° adjustable exhaust
- Integrated sound absorption
- Ergonomic handgrip, insulated against cold
- Reinforced head piece
- Dust and dirt protection

Applications

Production of pallets, crates and wooden boxes, packings for heavy load and export packaging




BeA DC/90-902C

Technical data



Article no.	12100696
EAN code	4045758120514
Magazine type	Top loader
Weight	3,6 kg
Measurements, mm	L 319, H 349, W 149
Safety system	Contact actuation
Fastener type	Nails type BDC
Magazine capacity	Max. 300 nails
Operating pressure	5 - 8 bar
Max. operating pressure	8 bar
Air consumption / operation	2 litres / 6 bar
Inner hose diameter	Ø 9 - 10mm LW recommended
Emission sound pressure level at the workstation	$L_{pA, 1s, d} = 101,1 \text{ dB}$
Single shot emission sound pressure level	$L_{WA, 1s, d} = 92,4 \text{ dB}$
Vibration level as per ISO 8662-11	is 4,56 m/s ² .
Accessories	Operating instructions, spare parts list, service instructions

Coilnägel BDC



BDC nails = wire collated coil nails	
Diameter	2,5 - 3,4 mm
Length	50 - 90 mm
Material	BK = steel, bright
	NK = steel, electro galv.
	RF = stainless steel, comparable with material 1.4301
	NR = stainless steel, comparable with material 1.4401
	FV = steel, hot dipped galvanized
Shaft	Smooth
	Ring
	Screw shank
Head type	Flat head
	Dome head
	PZ head
	TX head

Further types available on request. Nails as per DIN 1052, as well as per EN 14592 (Eurocode 5) are available.

Joh. Friedrich Behrens AG
Industrielle Befestigungssysteme
Bogenstrasss 43 - 45
22926 Ahrensburg
Germany

Further information:
Tel: + 49(0) 41 02 78 - 444
Fax + 49 (0) 41 02 78 - 270
info@behrens-group.com
www.bea-group.com

BeA is member of the following associations:

