

Pneumatic Plier Type 380/16-419

The BeA Pneumatic Plier 380/16-419 guarantees secure of a variety of materials. The pressure of the clinching jaw is controlled so that the work material is gently pressed against prior to the staple being driven. The deep jaw throat allows fastening even in hard to reach area.

The plier drives staples type 80/380 in the length of 6 to 16 mm.



Popular applications:

Clinching of: Paper, cardboard, foil, leather, bag headers etc.

Length: 210 mm
Width: 50 mm
Height: 216 mm

Technical data

| | |
|---|-------------------------------|
| Type description: | 380/16-419 Standard |
| Article code: | 12000062 |
| Magazine type : | Bottom loader |
| Safety: | Type 80 / 380 |
| Fastener type: | 160 |
| Magazine capacity: | 1 x 150 |
| Fasteners per strip: | 5 – 6 bar |
| Operating pressure: | 6 bar |
| Max. operating pressure: | 0.7 liters / 6 bar |
| Trigger frequency: | Ø 9 mm LW recommended |
| Air consumption/operation: | L pA, 1s, d= 86 dB |
| Inner hose diameter: | L WA, 1 s,d= 92 dB |
| Emission sound pressure level at the workstation: | 1.4 kg |
| Single-shot emission sound pressure level: | |
| Weight: | |

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

| | |
|--|---|
| Extras supplied with the stapler: | Operating instructions, spare parts list, service instructions, allen keys SW 8, SW 13, silencer. |
| | Subject to technical modifications. |

Accessories:

| Article code | Description |
|--------------|-----------------------------------|
| 14406013 | Carton support |
| 14400437 | Back nose assembly set (6 mm) |
| 14403705 | Back nose assembly set (Standard) |
| 14405273 | Jaw with 100 mm insertion depth |

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Stapler Type 380/16-419

Staples type 80 and type 380



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



| Description | L = Length mm |
|-------------|------------------|
| 380/06 NK | 6 |
| 380/08 NK | 8 |
| 380/10 NK | 10 |
| 380/12 NK | 12 |
| 380/14 NK | 14 |
| 380/16 NKS | 16 |

Other lengths and finishes are also available on request.

Explanations:

| | | | |
|------------------------------------|--------------------------------|--|----------------------|
| NK = galvanized steel | BK = bright steel | LM = aluminium | HZ = resin coated |
| NKS = galvanized steel, extra hard | BKS = bright steel, extra hard | NR = stainless steel, material. 1.4401 | DP = divergent point |
| NKH = galvanized steel, hard | MS = brass | RF = rust resistant, material 1.4301 | SA = step cut |