

Fastening technologies for industry



Corrugated Nailer WM 12-156

12000126



Fastener type

BeA Corrugated nails WM · Length: 6 - 12 mm

Product strengths

· Adjustable ventilation

Scope of operation

Carpentry, Measurement and assembly construction, Timber construction, Timber frame construction, Window and door construction

Scope of delivery

Sparepart list, User manual



More details:

Technical data

EAN	4045759001256
Type of fastener	BeA Corrugated nails WM
Fastener length min	6 mm
Fastener length max	12 mm
Magazine capacity max	75 pc
Weight	2,8 kg
Driving system	Compressed air
Activation method	Contact activation
Operating pressure min	6 bar
Operating pressure max	8 bar
Air consumption per drive operation	1,5 l (6 bar)
Tool length	90 mm
Tool width	70 mm
Tool height	261 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	79 dB(A)
Noise characteristic L WA. 1s, d according to EN 12549	87 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value and according to ISO 8662	4 m/s²
Weight incl. packaging	3,04 kg

Related fastener



BeA Corrugated nails WM · Length: 6 - 12 mm

Item No.	Diameter x Length	Nail shank	Material
10800000	6 mm	Corrugated	Steel, bright
10800002	9 mm	Corrugated	Steel, bright
10800004	12 mm	Corrugated	Steel, bright

Other variations and sizes on request