

Coil Nailer 556DC DPN

12100609



Fastener type

- BeA Nails DPN
- Diameter: 3,1 mm
- Length: 19 - 45 mm

Product strengths

- Adjustable depth setting
- Adjustable ventilation
- Contact release
- Safety yoke with large surface area

Scope of operation

Carpentry, Roofing and facade

Scope of delivery

Sparepart list, User manual

More details:




Technical data

EAN	4045759056492
Type of fastener	BeA Nails DPN
Fastener diameter min	3,1 mm
Fastener diameter max	3,1 mm
Fastener length min	19 mm
Fastener length max	45 mm
Tool magazin slope	16 °
Magazine capacity max	1 coil
Weight	2,25 kg
Driving system	Compressed air
Activation method	Contact activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	1,06 l (7 bar)
Depth adjustment	Yes
Tool length	287 mm
Tool width	116 mm
Tool height	273 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	99,9 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	102,9 dB(A)

Technical data

Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	2,53 m/s ²
Vibration value Ka according to ISO 8662	1,26 m/s ²
Weight incl. packaging	3,5 kg

Related fastener



BeA Nails DPN

- Diameter: 3,1 mm
- Length: 19 - 45 mm

Item No.	Diameter x Length	Nail shank	Material
10500001	3,1 mm x 19 mm	Smooth shank	Steel, galvanized
10500002	3,1 mm x 19 mm	Smooth shank	Steel, hot-dip galvanized
10500004	3,1 mm x 22 mm	Smooth shank	Steel, galvanized
10500005	3,1 mm x 22 mm	Smooth shank	Steel, hot-dip galvanized
10500007	3,1 mm x 25 mm	Smooth shank	Steel, galvanized
10500008	3,1 mm x 25 mm	Smooth shank	Steel, hot-dip galvanized
10500010	3,1 mm x 32 mm	Smooth shank	Steel, galvanized
10500011	3,1 mm x 32 mm	Smooth shank	Steel, hot-dip galvanized
10500013	3,1 mm x 38 mm	Smooth shank	Steel, galvanized
10500014	3,1 mm x 38 mm	Smooth shank	Steel, hot-dip galvanized
10500016	3,1 mm x 45 mm	Smooth shank	Steel, galvanized
10500597	3,1 mm x 25 mm	Ring shank	Steel, galvanized
10500941	3,1 mm x 25 mm	Ring shank	Stainless Steel (AISI 304, EN grade 1.4301, A2)
10501764	3,1 mm x 19 mm	Smooth shank	Steel, galvanized
10501765	3,1 mm x 25 mm	Smooth shank	Steel, galvanized
10501766	3,1 mm x 32 mm	Smooth shank	Steel, galvanized
10502019	3,1 mm x 32 mm	Smooth shank	Steel, hot-dip galvanized
10502163	3,1 mm x 45 mm	Smooth shank	Steel, hot-dip galvanized

Other variations and sizes on request